



# RECESSED COMMERCIAL AIR CURTAINS

## COR-FT Series

**NEW**



Especially designed for installations into ceilings.

### Characteristics:

To be fitted to a height of up to 4 m.  
High-performance, low-noise tangential impeller.  
Can be fitted in series.

**Applications:** see page BASIC CONCEPTS AIR CURTAINS.

**On request:** Grille is not included with the air curtain. Can be supplied in different colours.



**CR-6/9 N**  
Remote control included with the product, to control up to 5 units of the same model in series.



Restaurants and cafes



CR-6/9 N power selector

### ■ Dimensions (mm)

Model 1000

Model 1500


**Side detail (mm)**

1000/1500 Series


**Grille dimensions (mm)**  
The grille is not included in the price. It must be ordered separately.

Model	Dimensions (mm)			
REJA COR-FT 1000	A: 438	B: 1.148	C: 393	D: 1.103
REJA COR-FT 1500	A: 438	B: 1.755	C: 393	D: 1.710

\* Consult delivery period and price for all other colours on the RAL chart.



Distance/air speed



Fitting height

### ■ Technical Characteristics

Model	Voltage (50 Hz) (V)	Heat power (kW)	Motor power (W)	Speeds	Airflow (m³/h)			output speed* (m/s) at 0,05 m	Maximum ØT (°C)				Sound pressure level** (dB(A))	Abs. current (A)	Temp fuse	Ambient / Hot air	Weight (kg)	Grille colour*** <small>(The grille is not included in the price. It must be ordered separately)</small>
					Speed				Max. power		Min. power							
					High	Medium	Low		Fast sp.	Slow sp.	Fast sp.	Slow sp.						
COR F-1000 FT	230		128	2	1665		1293	10,70					59	0,55	•	A	20	White RAL 9016 or Aluminium
COR F-1500 FT	230		164	2	2581		2275	10,10					61	0,71	•	A	30	White RAL 9016 or Aluminium
COR-6-1000 FT	3N 400	3 / 6	128	3	1564	1336	1034	10,06	16,70	20,80	9,80	11,90	59,5	8,6	•	A / H	24	White RAL 9016 or Aluminium
COR-9-1000 FT	3N 400	4,5 / 9	128	3	1564	1336	1034	10,06	25	29,5	18	19	59,5	13	•	A / H	24	White RAL 9016 or Aluminium
COR-9-1500 FT	3N 400	4,5 / 9	166	3	2392	2109	1728	11,76	15,67	20,72	8,13	12,15	61,5	13	•	A / H	35	White RAL 9016 or Aluminium
COR-12-1500 FT	3N 400	6 / 12	166	3	2392	2109	1728	17	21	26,5	15	18	61,5	17,3	•	A / H	35	White RAL 9016 or Aluminium

\* Maximum speed.

\*\* Measured at a distance of 3 m in free field.

\*\*\* Standard Colors. Also available on-demand grille in black RAL 9005 without price increase. Consult delivery period and price for all other colours on the RAL chart.