

SINGLE PHASE SPEED CONTROLLER

Electrical accessories

REB-5

Electronic single phase speed controller Surface mounted.



Fuse protected.
Minimum speed adjustment.
Separate On/ Off switch. LxAxH (mm): **83x81x160**

Model	Electrical supply		IP Protection	Power (VA)	Maximum current (A)	Class	Operating temperature range
	Frequency (Hz)	Voltage (V)					
REB-5	50	230V	IP54	1150	5	I (⏚)	5-35°C

Accessories

REB-10

Electronic single phase speed controller Surface mounted.



Fuse protected.
Minimum speed adjustment.
Separate On/ Off switch. LxAxH (mm): **115x95x195**

Model	Electrical supply		IP Protection	Power (VA)	Maximum current (A)	Class	Operating temperature range
	Frequency (Hz)	Voltage (V)					
REB-10	50	230V	IP54	2300	10	I (⏚)	5-35°C

RRB-100

Electromechanical single-phase speed controller



Variable reactance.
Surface mounted.
Five position knob. LxAxH (mm): **90 x 54 x 134**

Model	Electrical supply		IP Protection	Power (VA)	Maximum current (A)	Class	Operating temperature range
	Frequency (Hz)	Voltage (V)					
RRB-100	50	230	IP20	94,3W	0,41	II (⏚)	5-45°C